

# SHED MASTER

OPENER FOR SMALL, EXPOSED AREAS



## An opener with versatility, no matter what the environment.

Automatic Technology's Shed Master operator is the ideal solution for exposed areas\*, such as perimeter doors and open carports. With a tough, IP24 rated weather resistant housing and a slim fit design, the Shed Master is suitable for even the tightest of spaces.

This rugged sheet door operator is fit for all. Standard features include Intelligent Safety Systems, Door Profiling and TrioCode™128 transmitter system ensuring optimum safety and security. The Shed Master comes with a keyed lockout feature which prevents unauthorized manual operation of the door. If you need a solution to last in all weather conditions, look no further than Shed Master.


### WHAT'S INCLUDED:



IP24 Weather Resistant Operator



Remote Transmitters



Keyed Lockout



3 - Wire Safety Beams



Wall Station

### AT A GLANCE:

#### SECURE & RELIABLE TRANSMITTERS



The TrioCode™128 remote control ensures secure and reliable access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol for the ultimate in security.

#### WEATHER-RESISTANT HOUSING

Designed for installation on covered exposed doors, this operator has a weather resistant rating of IP24.

#### KEYED & ELECTRONIC LOCKOUT

As the Shed Master can be installed in exposed\* locations, a keyed lockout is included to stop unwanted persons reaching over the fence and disengaging the door to manual mode. Also, the control panel can be similarly locked out to prevent unauthorized usage.

#### INTELLIGENCE

Built-in intelligent features such as Intelligent Safety System and Door Profiling – meaning the door adjusts itself when opening and closing or if blocked.

\*Operator must be covered if door is outdoors. (eg. pelmet)

# TECHNICAL SPECIFICATIONS



## SHED MASTER

<b>Power</b>	Input Voltage	120Va.c. 60Hz
	Short-term Lifting Force	550N
<b>Installation</b>	Max Door Area <sup>1</sup>	165ft (12" high)
	Install side	Left or right hand side installation
<b>Transmitter System</b>	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	Code hopping (Non-linear encryption algorithm)
	Code Combinations	3.4x10 <sup>38</sup> code combinations
	Transmitter Type	TrioCode™128
	Transmitter Capacity (x 4-button registers)	8
<b>Additional Features</b>	Courtesy Light	Optional
	Weather Resistance Rating	IP24
	Lockout System	Keyed lockout for manual release
		Electronic lockout for control panel buttons
	Mini door extension kit	Optional
	Safety Beam Compatibility	1 x 3-wire Safety Beam
<b>Warranty*</b>	2 years/5,000 cycles	

### SAFETY & SECURITY FEATURES

- Intelligent Safety System
- Door Profiling
- TrioCode™128

### POWER & MOUNTING SYSTEM

- DC Motor – 1000N
- Slim Fit

### OPERATING MODES

- Weather Resistant
- Service Indicator
- Lockout System

### OPTIONS AND UPGRADES



WIRELESS KEYPAD



MINI DOOR EXTENSION KIT



1. Typical sheet door opening heights:  
9.5" drum = 9' / 12" drum = 12'

For more product information, visit [www.automatictechnology.com](http://www.automatictechnology.com)

©2025 Automatic Technology America LLC. The Automatic Technology logos & TrioCode™ are registered trademarks. In an ongoing commitment to product quality, the specifications may change from time to time – E&OE Automatic Technology LLC, 28610 US-290 Suite F09-345, Cypress, TX 77433, United States, [www.automatictechnology.com](http://www.automatictechnology.com), 1-800-934-9892. \*Please see full warranty terms and conditions at [www.automatictechnology.com](http://www.automatictechnology.com). This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under American Law. Date: August 2025

